

Compliance Document

No. D 075386 0156 Rev. 00

Holder of Certificate: **Shenzhen Kstar New Energy Company Limited**
The 9th Floor, R&D Building
Kstar Industrial Park, Guangming Hi-tech Industrial Zone
518107 Shenzhen, Guangdong Province
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter
(Hybrid Inverter)**

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290213009401

Date, 2021-05-26



(Billy Qiu)

Compliance Document

No. D 075386 0156 Rev. 00

Model(s): **BluE-S 3680D, BluE-S 5000D,
BluE-S 3680D-M1, BluE-S 5000D-M1**

Parameters:

Model	BluE-S 3680D	BluE-S 5000D	BluE-S 3680D-M1	BluE-S 5000D-M1
PV terminal				
Vmax. PV	580Vd.c.		580Vd.c.	
Rate Voltage	400Vd.c.		400Vd.c.	
MPPT Voltage Range	120~550Vd.c.		80-560Vd.c.	
MPPT Voltage Range (full load)	184 ~ 550Vd.c.	230 ~ 550Vd.c.	165 ~ 520Vd.c.	210 ~ 520Vd.c.
MPPT Tracker number	2			
Max. continuous PV input current per tracker	13Ad.c.		15Ad.c.	
Isc PV per tracker	16Ad.c.		18Ad.c.	
Max. continuous PV input power	4800W	6500W	4800W	6500W
Battery terminal				
Battery type	Lithium or lead-acid batteries			
Voltage range	40~60Vd.c.			
Rated voltage	48Vd.c.			
Maximum charge/ discharge current	50Ad.c./ 80Ad.c.	100Ad.c./ 100Ad.c.	50Ad.c./ 80Ad.c.	100Ad.c./ 100Ad.c.
Maximum charge/ discharge power	3000W/ 4000W	4600W/ 5000W	3000W/ 4000W	4600W/ 5000W
Grid terminal parameter				
Rated voltage	230Va.c.			
Rated frequency	50Hz			
Rated input Current	31Aa.c.			
Maximum continuous input current	32Aa.c.			
Maximum continuous input power	7360VA			
Rated output Current	16Aa.c.	22Aa.c.	16Aa.c.	22Aa.c.
Maximum continuous output current	16Aa.c.	22Aa.c.	16Aa.c.	22Aa.c.
Power factor (Cos phi), adjustable	0.8 leading ~0.8 lagging			
Maximum continuous output power	3680VA	5000VA	3680VA	5000VA
Back up load terminal parameter				
Rated voltage	230Va.c.			
Rated frequency	50Hz			
Rated output Current	16Aa.c.	20Aa.c.	16Aa.c.	20Aa.c.
Maximum continuous output current	16Aa.c.	20Aa.c.	16Aa.c.	20Aa.c.
Rated continuous output power	3680W	4600W	3680W	4600W
Maximum output apparent power	4000VA	5000VA	4000VA	5000VA



Compliance Document

No. D 075386 0156 Rev. 00

**Tested
according to:**

C10/11:2021